

Low-Cost CuX Catalyst from Blast Furnace Slag Waste for Low-Temperature NH₃-SCRL. Chen^{1,2}, S. Ren¹, Q. Liu¹, D. Ferri²¹Chongqing University, ²Paul Scherrer Institut

The presence of nitrogen oxides (NO_x) in industrial flue gas is a major concern due to their negative impact on the environment and human health [1]. Selective catalytic reduction with NH₃ (NH₃-SCR) is the primary technology for reducing and controlling NO_x emissions [2]. As one of the primary solid wastes generated from blast furnace iron production, blast furnace slag (BFS) contains an adequate quantity of Al₂O₃ and SiO₂ that could serve as raw material for zeolite synthesis. Zeolite X with low Si/Al ratio was successfully prepared by the seed-hydrothermal method [3].

In this study, we investigated the low-temperature NH₃-SCR activity and surface acidity of a series of Cu-exchanged zeolite X (derived from blast furnace slag) catalysts with various Cu/Al ratios (mole ratio of Cu/Al=0.13, 0.28, 0.4, 0.45, 0.46, 0.47). Based on the NH₃-SCR performance of these CuX catalysts, the CuX-0.28 catalyst exhibited the highest NH₃-SCR activity across the entire temperature range, exhibiting NO conversion above 93% from 150 °C to 400 °C and N₂ selectivity higher than 91%. The catalytic tests towards the oxidation of NH₃ revealed that NH₃ was oxidized to NO or N₂O above 300 °C. NH₃-TPD measurements showed that the CuX-0.28 catalyst had the highest surface acidity in the series and most of surface acidity was attributed to Lewis acid sites. During in situ DRIFTS of the NH₃-SCR reaction, both Lewis and Brønsted acid sites were identified on the CuX-0.28 catalyst, with Lewis acid sites playing the primary role in the NH₃-SCR reaction.

[1] S. C. Anenberg, et al. *Nature*, **2017**, *545*, 467-471.

[2] Y. Park, et al. *Chemical Engineering Journal*, **2023**, *461*, 141958.

[3] L. Chen, et al. *ACS Sustainable Chemistry & Engineering*, **2022**, *10*, 7739-7751.